

## AXIperfect FXXL WB 415 - 435 Wp

High performance solar module  
108 halfcell, N-Type TOPCon


### The advantages:

- 15** Years 15 years Manufacturer's warranty
- 30** Years 30 years Performance guarantee
- HC** High module performance through Half-Cut-technology and selected materials
- Wp** Guaranteed positive power tolerance from 0-5 Wp by individual measurement
- 100%** 100% visual electroluminescence inspection in production
- IP 68** High quality junction box and connector systems
- TOP** More performance through innovative N-Type TOPCon-Technology



Fig. similar 08TFMEN231116A

### Exclusive linear AXITEC high performance guarantee!



## AXIperfect FXXL WB 415 - 435 Wp

**Electrical data** (at standard conditions (STC) irradiance 1000 watt/m<sup>2</sup>, spectrum AM 1.5 at a cell temperature of 25°C)

Type	Nominal output P <sub>mpp</sub>	Nominal voltage U <sub>mpp</sub>	Nominal current I <sub>mpp</sub>	Short circuit current I <sub>sc</sub>	Open circuit voltage U <sub>oc</sub>	Module conversion efficiency
AC-415TFM/108WB	415 Wp	31.32 V	13.26 A	13.99 A	37.92 V	21.25 %
AC-420TFM/108WB	420 Wp	31.51 V	13.33 A	14.07 A	38.11 V	21.51 %
AC-425TFM/108WB	425 Wp	31.70 V	13.41 A	14.15 A	38.30 V	21.76 %
AC-430TFM/108WB	430 Wp	31.88 V	13.49 A	14.23 A	38.49 V	22.02 %
AC-435TFM/108WB	435 Wp	32.06 V	13.57 A	14.32 A	38.63 V	22.28 %

### Design

Frontside	3.2 mm hardened, low-reflection white glass
Cells	108 N-Type TOPCon high efficiency cells
Backside	Composite film
Frame	30 mm black aluminium frame

### Mechanical data

L x W x H	1722 x 1134 x 30 mm
Weight	21.8 kg with frame

### Mechanical load

Design load (pressure/suction)	3600 Pa / 1600 Pa
Test load (pressure/suction)	5400 Pa / 2400 Pa

### Power connection

Socket	Protection Class IP68, 3 bypass diodes
Wire	approx. 1.2 m, 4 mm <sup>2</sup>
Plug-in system	IP68, MC4-EVO 2, MC4-EVO 2A, JM608

### Limit values

System voltage	1500 VDC
NOCT (nominal operating cell temperature)*	45°C +/-2K
Reverse current feed IR	25.0 A

### Permissible operating

temperature	-40°C to 85°C / -40F to 185F
Fire class / Protection class	C (UL790) / II

(No external voltages greater than U<sub>oc</sub> may be applied to the module)

\* NOCT, irradiance 800 W/m<sup>2</sup>; AM 1,5; wind speed 1 m/s; Temperature 20°C

### Temperature coefficients

Voltage U <sub>oc</sub>	-0.26 %/K
Current I <sub>sc</sub>	0.047 %/K
Output P <sub>mpp</sub>	-0.31 %/K

### Low-light performance

 (Example for AC-435TFM/108WB)

I-U characteristic curve	Current I <sub>pp</sub>	Voltage U <sub>pp</sub>
200 W/m <sup>2</sup>	2.77 A	34.65 V
400 W/m <sup>2</sup>	5.59 A	31.21 V
600 W/m <sup>2</sup>	8.36 A	31.45 V
800 W/m <sup>2</sup>	11.05 A	31.72 V
1000 W/m <sup>2</sup>	13.57 A	32.06 V

### Packaging

Module pieces per pallet	36
Module pieces per HC-container	936




Fig. principle sketch

All dimensions in mm

