

# JW-HT108N

N-type Single Glass Mono Module

## 415-435W

J-TOPCon 2.0 Technology



**435W**  
Maximum Power Output

**22.27%**  
Maximum Module Efficiency

**0~+5W**  
Power Output Tolerance

IEC61215(2016), IEC61730(2016) | ISO9001:2015: Quality Management System | ISO14001:2015: Environment Management System  
ISO45001:2018: Occupational health and safety management systems | IEC62941: 2019: Quality system for PV module manufacturing



**High Power Output**  
SMBB technology reduces the distance between busbars and finger grid lines, improving reliability and increasing output



**Better Weak Illumination Response**  
Higher power output even under low-light environments, like on cloudy or foggy days



**ZERO LID (Light Induced Degradation)**  
N-type solar cell has no LID naturally which can increase power generation



**Better Temperature Coefficient**  
Higher power generation under working conditions, thanks to passivating contact cell technology



**Higher Reliability**  
Adopted Jolywood's latest J-TOPCon 2.0 technology: No polysilicon wrap around, full electrical isolation, and zero leakage current increase safety on rooftop




**Lighter Module Weight**  
Reduces weight by more than 20% compared to bifacial double glass module

### Jolywood Delivers Reliable Performance Over Time

- Leading N-type module manufacturer
- Fully automated facility and industry-leading technology
- Best-in-class durability and reliability
- BloombergNEF Tier One

### Linear Performance Warranty



\*Subject to the terms and conditions contained in the applicable Jolywood Solar Limited Warranty Statement. Also this 25-year limited product warranty is available only for products installed and operating on residential rooftops in certain regions.

## Electrical Properties | STC\*

Testing Condition	Front Side	Front Side	Front Side	Front Side	Front Side
Peak Power (Pmax) (W)	415	420	425	430	435
MPP Voltage (Vmp) (V)	31.7	31.9	32.1	32.3	32.5
MPP Current (Imp) (A)	13.10	13.17	13.24	13.32	13.39
Open Circuit Voltage (Voc) (V)	37.7	37.9	38.1	38.3	38.4
Short Circuit Current (Isc) (A)	13.91	13.98	14.05	14.12	14.18
Module Efficiency (%)	21.25	21.51	21.76	22.02	22.27

\*STC: Irradiance 1000 W/m<sup>2</sup>, Cell Temperature 25°C, AM1.5  
The data above is for reference only and the actual data is in accordance with the practical testing Power Measurement Tolerance ±3%

## Electrical Properties | NOCT\*

Testing Condition	Front Side	Front Side	Front Side	Front Side	Front Side
Peak Power (Pmax) (W)	315	318	322	325	330
MPP Voltage (Vmp) (V)	29.8	29.9	30.1	30.3	30.5
MPP Current (Imp) (A)	10.56	10.62	10.67	10.74	10.82
Open Circuit Voltage (Voc) (V)	36.0	36.2	36.4	36.6	36.8
Short Circuit Current (Isc) (A)	11.22	11.27	11.33	11.38	11.44

\*NOCT: Irradiance 800 W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1 m/s

## Operating Properties

Operating Temperature (°C)	-40°C~+85°C
Maximum System Voltage (V)	1500V DC (IEC)
Maximum Series Fuse Rating (A)	30
Power Tolerance	0~+5W

## Temperature Coefficient

Temperature Coefficient of Pmax*	-0.300%/°C
Temperature Coefficient of Voc	-0.250%/°C
Temperature Coefficient of Isc	+0.045%/°C
Nominal Operating Cell Temperature (NOCT)	42±2°C

\*Temperature Coefficient of Pmax±0.03%/°C

## Mechanical Properties


Cell Size	182.00mm*91.00mm
Number of Cells	108pcs(12*9)
Module Dimension	1722mm*1134mm*30mm
Weight	21.5kg
Front Glass*	3.2mm
Frame	Anodized Aluminium Alloy
Junction Box	IP68 (3 diodes)
Length of Cable	4.0mm <sup>2</sup> , +300mm/-180mm (Cable length can be customized)

\*Heat strengthened glass




## Partner Section

NOTE :

## Engineering Drawing (unit: mm)



## Characteristic Curves | HT108N-420



## Packaging Configuration

Packing Type	20'GP	40'GP	40'HQ
Piece/Pallet		36	
Pallet/Container	6	13	26
Piece/Container	216	468	936

\*The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to ongoing innovation, R&D enhancement, Jolywood (Taizhou) Solar Technology Co., Ltd. reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.

